Isofield Vista Hood with Facemask

Sterile Cleanroom Hood with Facemask

PRODUCT INFO

Postbox-style sterile cleanroom hood with integrated tie-on facemask

Half-face elastic for additional comfort

Flat-top design ensures excellent forehead coverage

STORAGE & SHELF LIFE

Store in a dry, cool place (<40°C) away from direct sunlight

Do not expose open cartons to prolonged direct fluorescent light

Five (5) years from date of manufacture



APPLICATIONS

Grade A & B and ISO Class 5 applications where fluid protection, viral barrier, low particle emissions required

Pharmaceutical product preparation

Cleanroom cleaning and preparation

Aseptic filling & labeling

Medical device manufacturing
Blending operations for biotechnologies

CLEANROOM COMPATIBILITY

GMP Grade A cleanroom
GMP Grade B cleanroom

ISO Class 4 cleanroom
ISO Class 5 cleanroom

Class 10 cleanroom
Class 100 cleanroom

QUALITY ASSURANCE

Manufactured in a facility operating under ISO 9001:2015 quality management system

Processed in a NEBB certified ISO Class 5 cleanroom

PACKAGING

1 piece inner bag,

20 inner bags per outer bag,

7 outer bags per carton (140 pieces)

Aseptic fold

PRODUCT CODE

REF **80911**

UNIVERSAL SIZE

40°C LATEX STERILE R

Last updated **20 Oct 2026**

MATERIAL PERFORMANCE PARAMETERS (HOOD)

DESCRIPTION	UNITS	METHOD	SPECIFICATION	TYPICAL
Basic weight	g/m^2	ISO 9073-1-1989	±2	60
Hydrostatic head	mmH_20	ISO 811-1981	≥100	213
Air permeability	$l/m^2/S$	GB/T5453	≥	2000
Surface resistivity	Ω	ASTM D257	Static dissipative	10^{10}

HELMKE DRUM TEST RESULT CLASS 1

PARTICLE SIZE	CUMULATIVE RELEASE RATE (COUNTS/MIN)	SPECIFICATION	CLASS	TEST METHOD
≥ 0.3µm	743*	Less than 2,000	1	IEST-RP-CC003.4
≥ 0.5µm	318*	2,000 - 20,000	1	IEST-RP-CC003.4
≥ 5.0µm	43*	20,000 - 200,000	1	IEST-RP-CC003.4

*Typical results

PERMEATION TEST AGAINST CHEMO DRUGS

CHEMOTHERAPY DRUGS	BREAKTHROUGH TIME	TEST METHOD
Carmustine	30 min	ASTM F739-20
Cisplatin	> 480 min	ASTM F739-20
Cyclophosphamide	> 480 min	ASTM F739-20
Doxorubicin HCl	> 480 min	ASTM F739-20
Etoposide	> 480 min	ASTM F739-20
Fluorouracil	> 480 min	ASTM F739-20
Methotrexate	> 480 min	ASTM F739-20
Paclitaxel	> 480 min	ASTM F739-20
Thiotepa	60 min	ASTM F739-20

*Results achieved under controlled laboratory conditions, by accredited ISO 17025 third party testing laboratory
**Mask not tested

TECHNICAL PROPERTIES

TEST REFERENCE	EXPLANATION	TEST RESULTS	
EN 14325:2004 EN ISO 6530:2005	Repellency to chemicals	10% Sodium hydroxide	Level 3
		30% Sulphuric acid	Level 3
		O-Xylene	Level 2
		Butan-1-ol	Level 2
		70% Isopropyl alcohol	Level 2
		70% Ethanol	Level 2
EN 14325:2004 EN ISO 6530:2005	Resistance to penetration by chemicals	10% Sodium hydroxide	Level 3
		30% Sulphuric acid	Level 3
		O-Xylene	Level 3
		Butan-1-ol	Level 3
		70% Isopropyl alcohol	Level 3
		70% Ethanol	Level 3
EN 14325:2004 EN ISO 9073-4:1997	Trapezoidal tear resistance	Machine direction	Class 2
		Cross direction	Class 2
EN 14325:2004 EN ISO 13934-1:2013	Tensile strength	Machine direction	Class 1
		Cross direction	Class 2
EN 14325:2004 EN ISO 12947-2:2016	Abrasion resistance	Class 2	
EN 14325:2004 EN ISO 7854:1997, Method B	Flex cracking resistance	Class 6	
EN 14325:2004 EN 863:1995	Puncture resistance	Class 1	
EN 14325:2004 [5.5]	Seam strength	Class 2	
EN 13034:2015 + A1:2009 ISO 17491-4:2008 (Type PB6)	Chemical protective coveralls have been tested to the whole suit testand Type PB(6) hoods and sleeves have not been tested to the whole suit test	-	
In-house AQL 1.5	Test plan for major defect	Pass	
EN ISO11137 Part 2:2015	Sterility validation	SAL 10^{-6}	

FACEMASK MATERIALS

Outer layer	Non-woven spunbond polyester
Filtration Layer	Non-woven meltblown polyester
Inner facing layer	Non-woven polypropylene / polyethylene
Tie-tapes	Non-woven polyester

FACEMASK FILTRATION PROPERTIES

Particle Filtration Efficiency (PFE) @ 0.1 Micron	94%
Bacterial Filtration Efficiency (BFE) @ 0.3 Micron	97%
Differential Pressure (ΔP), mm H_20/cm^2	6.8



LOADING

	EURO-PALLET	STANDARD PALLET
Pallet size	W80 L120cm	W100 L120cm
Gross weight	7.29kg	7.29kg
Carton size	W28 L43 H31cm	W28 L43 H31cm
Nett weight	4.82kg	4.82kg
Air freight pallet	Max height: 139cm Layers: 4 Cartons: 24	Max height: 139cm Layers: 4 Cartons: 32
Sea freight pallet	Max height: 170cm Layers: 5 Cartons: 30	Max height: 170cm Layers: 5 Cartons: 40

DOCUMENTATION

CERTIFICATE OF CONFORMANCE (COC)
CERTIFICATE OF ANALYSIS (COA)
CERTIFICATE OF PROCESSING (COP)

View sample of COC, COA, COP

FACTORY RELATED CERTIFICATIONS

To request ISO9001 Certificate, please email us



Country of Origin: China
HS Code: 6210109000

This data sheet and any other claims made by or on behalf of Isofield shall not be taken as a warranty of merchantability or as a statement that any Isofield products are suitable for a specific purpose. Isofield shall not be held responsible for the end user's choice of product for a particular application.

EUROPE

ISOFIELD (IRELAND) LTD
Charter House, 5 Pembroke Row, Dublin 2
Dublin, D02 FW61, Ireland

ASIA

ISOFIELD SDN BHD
6 Jalan Gudang 16/9, Seksyen 16, 40200, Shah Alam,
Selangor, Malaysia, T +603 5512 1709

CONTACT

www.isofield.com
enquiries@isofield.com