

Isofield Atto 230

Irradiated Tie-On Cleanroom Facemask with Anti-Fog Visor

Last updated 28 Mar 2024



EF 60521 ZE UNIVERSAL



Irradiated tie-on Cleanroom facemask with anti-fog visor 3-layer non-woven configuration Threaded top ties to ensure secure fit to face Anti-fog-coated visor

Highly efficient bacterial and particle filtration Particle Shedding (Helmke Drum) Category I*

IPA resistant ink pouches to maintain traceability

*mask only

APPLICATIONS 🗳

Pharmaceutical product preparation Cleanroom cleaning Medical device manufacturing Blending operations Handling of active materials Cleanroom equipment maintenance

CLEANROOM COMPATIBILITY

GMP Grade A cleanroom GMP Grade B cleanroom ISO Class 4 cleanroom ISO Class 5 cleanroom Class 10 cleanroom Class 100 cleanroom

QUALITY ASSURANCE 🧔

Manufactured in a facility operating under an ISO 9001:2015 quality management system Processed in a NEBB certified ISO Class 5 cleanroom

STORAGE & SHELF LIFE 🛅

Store in a cool, dry place (< 40°C) away from direct sunlight Do not expose open cartons to prolonged direct fluorescent light Five (5) years from date of manufacture

PACKAGING 📃

1 piece per sealed inner PE bag, 25 inner bags per sealed outer PE bag, 8 outer bags per lined carton (200 pieces)

PHYSICAL PROPERTIES

LENGTH	WIDTH	COLOUR	STYLE
230mm (± 5mm)	95mm (± 5mm)	White	Tie-On

MATERIALS

Outer layer	Non-woven spunbond polyester
Filtration Layer	Non-woven meltblown polyester
Inner facing layer	Non-woven polypropylene / polyethylene
Tie-tapes	Non-woven polyester
Visor	Anti-fog PET

FILTRATION PROPERTIES

Particle Filtration Efficiency (PFE) @ 0.1 Micron	94%
Bacterial Filtration Efficiency (BFE) @ 0.3 Micron	97%
Differential Pressure (ΔP), mm H₂0/cm²	6.8

TECHNICAL PROPERTIES

Sterilization	EN ISO 11137	Product irradiated and provided with Certificate Of Irradiation (COI)
Particle Generation Test by Helmke Drum	IEST-RP-CC003.4*	Specifies methods for particle shed analysis in Helmke Drum applications
NORM	TEST REFERENCE	EXPLANATION

*Test performed on mask only



LOADING

	EURO-PALLET	STANDARD PALLET
Pallet size	W80 L120cm	W100 L120cm
Gross weight	5.02kg	5.02kg
Carton size	W28 L32 H30cm	W28 L32 H30cm
Nett weight	3.22kg	3.22kg
Air freight pallet	Max height: 135cm Layers: 4 Cartons: 32	Max height: 135cm Layers: 4 Cartons: 48
Sea freight pallet	Max height: 165cm Layers: 5 Cartons: 40	Max height: 165cm Layers: 5 Cartons: 60

DOCUMENTATION



CERTIFICATE OF CONFORMANCE (COC) CERTIFICATE OF ANALYSIS (COA) CERTIFICATE OF IRRADIATION (COI)

View sample of COC, COA, COI



FACTORY RELATED CERTIFICATIONS To request ISO9001 Certificate, please email us

Country of origin: **China** HS Code: 6307909000

This data sheet and any other claims made by or on behalf of Isofield shall not be taken as a warranty of merchantability or as a statement that any Isofield products are suitable for a specific purpose. Isofield shall not be held responsible for the end user's choice of product for a particular application.

EUROPE

ASIA

ISOFIELD (IRELAND) LTD 70 Northumberland Road, Ballsbridge Dublin 4, Ireland T +44 (0) 1638 6762 39 ISOFIELD SDN BHD 6 Jalan Gudang 16/9, Seksyen 16, 40200, Shah Alam, Selangor, Malaysia, T +603 5512 1709 CONTACT

www.isofield.com info@isofield.com

sofield