

Isofield Horizon Coverall with Mandarin Collar

Non-sterile Cleanroom coverall with mandarin collar

PRODUCT INFO

Two-layer mandarin collar provides secure fit at neck area

Zip flap with double-sided tape prevents ingress and egress of particles

Low-linting, anti-static fabric suitable for chemo handling

Elasticated thumb loops

Back elastic to prevent bellows effect

STORAGE & SHELF LIFE

Store in a dry, cool place (<40°C) away from direct sunlight

Do not expose open cartons to prolonged direct fluorescent light

Five (5) years from date of manufacture

APPLICATIONS

Medical device production and assembly

Cleanroom cleaning & preparation

Semiconductor & wafer fabrication

Electric vehicle (EV) & battery assembly

CLEANROOM COMPATIBILITY

ISO Class 4 cleanroom
ISO Class 5 cleanroom

Class 10 cleanroom
Class 100 cleanroom

QUALITY ASSURANCE

PPE Cat III, Type 5/6 certified

Manufactured in a facility operating under ISO 9001:2015 quality management system

Processed in a NEBB certified ISO Class 5 cleanroom

PACKAGING

1 piece per sealed inner bag,

1 inner bag per sealed outer bag,

20 outer bags per carton liner with twist tie (XS-XXL),

15 outer bags per carton liner with twist tie (3XL-4XL)

 Aseptically folded



PRODUCT CODE

REF
80820

XSMALL	80820XS	XLARGE	80820XL
SMALL	80820S	XXLARGE	80820XXL
MEDIUM	80820M	3XLARGE	80820XXXL
LARGE	80820L	4XLARGE	80820XXXXL

CE 2797          



Mandarin collar

Back elastic to prevent bellows effect



Thumbloop for easy donning

MATERIAL PERFORMANCE PARAMETERS

DESCRIPTION	UNITS	METHOD	SPECIFICATION	TYPICAL
Basic weight PP/PE film laminate	g/m ²	ISO 9073-1-1989	±2	60
Hydrostatic head	mmH ₂ O	ISO 811-1981	≥100	213
Air permeability	l/m ² /S	GB/T5453	≥	2000
Surface resistivity	Ω / sq	ASTM D257	Static dissipative	10 ¹⁰

HELMKE DRUM TEST RESULT CLASS 1

PARTICLE SIZE	CUMULATIVE RELEASE RATE (COUNTS/MIN)	SPECIFICATION	CLASS	TEST METHOD
≥ 0.3µm	743*	Less than 2,000	1	IEST-RP-CC003.4
≥ 0.5µm	318*	2,000 - 20,000	1	IEST-RP-CC003.4
≥ 5.0µm	43*	20,000 - 200,000	1	IEST-RP-CC003.4

*Typical results

PERMEATION TEST AGAINST CHEMO DRUGS

CHEMOTHERAPY DRUGS	BREAKTHROUGH TIME	TEST METHOD
Carmustine	30 min	ASTM F739-20
Cisplatin	> 480 min	ASTM F739-20
Cyclophosphamide	> 480 min	ASTM F739-20
Doxorubicin HCl	> 480 min	ASTM F739-20
Etoposide	> 480 min	ASTM F739-20
Fluorouracil	> 480 min	ASTM F739-20
Methotrexate	> 480 min	ASTM F739-20
Paclitaxel	> 480 min	ASTM F739-20
Thiotepa	60 min	ASTM F739-20

*Results achieved under controlled laboratory conditions, by accredited ISO 17025 third party testing laboratory

TECHNICAL PROPERTIES

TEST REFERENCE	EXPLANATION	TEST RESULTS
EN 14325:2004 EN ISO 6530:2005	Repellency to chemicals	10% Sodium hydroxide Level 3
		30% Sulphuric acid Level 3
		O-Xylene Level 2
		Butan-1-ol Level 2
		70% Isopropyl alcohol Level 2
		70% Ethanol Level 2
EN 14325:2004 EN ISO 6530:2005	Resistance to penetration by chemicals	10% Sodium hydroxide Level 3
		30% Sulphuric acid Level 3
		O-Xylene Level 3
		Butan-1-ol Level 3
		70% Isopropyl alcohol Level 3
		70% Ethanol Level 3
EN 14325:2004 EN ISO 9073-4:1997	Trapezoidal tear resistance	Machine direction Class 2
		Cross direction Class 2
EN 14325:2004 EN ISO 13934-1:2013	Tensile strength	Machine direction Class 1
		Cross direction Class 2
EN ISO 13982- 2:2004 EN ISO 13982- 1:2004 (Type 5)	Inward leakage of aerosols and fine particles into suits	Pass
		IL _{82/90} 0.544%
		IL _{8/10} 0.233%
EN 14325:2004 EN ISO 12947-2:2016	Abrasion resistance	Class 2
EN 14325:2004 EN ISO 7854:1997, Method B	Flex cracking resistance	Class 6
EN 14325:2004 EN 863:1995	Puncture resistance	Class 1
EN 14325:2004 [5.5]	Seam strength	Class 2
EN 13034:2015 + A1:2009 ISO 17491-4:2008 (Type 6)	Resistance to penetration by a spray of liquid (Spray Test)	Pass
In-house AQL 1.5	Test plan for major defect	Pass

LOADING

	EURO-PALLET	STANDARD PALLET
Pallet size	W80 L120cm	W100 L120cm
Gross weight	4.55 - 6.28kg	4.55 - 6.28kg
Carton size	W28 L43 H31cm	W28 L43 H31cm
Nett weight	3.77 - 5.50kg	3.77 - 5.50kg
Air freight pallet	Max height: 139cm Layers: 4 Cartons: 24	Max height: 139cm Layers: 4 Cartons: 32
Sea freight pallet	Max height: 170cm Layers: 5 Cartons: 30	Max height: 170cm Layers: 5 Cartons: 40

DOCUMENTATION



CERTIFICATE OF CONFORMANCE (COC)
CERTIFICATE OF ANALYSIS (COA)

Please [email us](#)



FACTORY RELATED CERTIFICATIONS
To request ISO9001 Certificate,
please [email us](#)



Country of origin: **China**
HS Code: 6210109000

This data sheet and any other claims made by or on behalf of Isofield shall not be taken as a warranty of merchantability or as a statement that any Isofield products are suitable for a specific purpose. Isofield shall not be held responsible for the end user's choice of product for a particular application.

EUROPE

ISOFIELD (IRELAND) LTD
70 Northumberland Road, Ballsbridge Dublin 4,
Ireland T +44 (0) 1638 6762 39

ASIA

ISOFIELD SDN BHD
6 Jalan Gudang 16/9, Seksyen 16, 40200, Shah Alam,
Selangor, Malaysia, T +603 5512 1709

CONTACT

www.isofield.com
info@isofield.com