

Isofield Vista Hood with Integrated Facemask

Sterile Cleanroom hood with integrated facemask

PRODUCT INFO

Postbox-style sterile cleanroom hood with integrated tie-on facemask

Half-face elastic for additional comfort

Flat-top design ensures excellent forehead coverage

APPLICATIONS

Grade A & B and ISO Class 5 applications where fluid protection, viral barrier, low particle emissions required

Pharmaceutical product preparation

Cleanroom cleaning and preparation

Aseptic filling & labeling

Medical device manufacturing

Blending operations for biotechnologies

QUALITY ASSURANCE

Manufactured in a facility operating under ISO 9001:2015 quality management system

Processed in a NEBB certified ISO Class 5 cleanroom

STORAGE & SHELF LIFE

Store in a dry, cool place (<40°C) away from direct sunlight

Do not expose open cartons to prolonged direct fluorescent light

Five (5) years from date of manufacture

CLEANROOM COMPATIBILITY

GMP Grade A cleanroom
GMP Grade B cleanroom

ISO Class 4 cleanroom
ISO Class 5 cleanroom

Class 10 cleanroom
Class 100 cleanroom

PACKAGING

1 piece per sealed inner bag,
20 inner bags per outer bag,
7 outer bags per carton liner with twist tie
140 pieces per carton

 Aseptically folded

PRODUCT CODE

REF 80911
UNIVERSAL SIZE



STERILE R

MATERIAL PERFORMANCE PARAMETERS (HOOD)

DESCRIPTION	UNITS	METHOD	SPECIFICATION	TYPICAL
Basic weight	g/m ²	ISO 9073-1-1989	±2	60
Hydrostatic head	mmH ₂ O	ISO 811-1981	≥100	213
Air permeability	l/m ² /S	GB/T5453	≥	2000
Surface resistivity	Ω	ASTM D257	Static dissipative	10 ¹⁰

HELMKE DRUM TEST RESULT CLASS 1

PARTICLE SIZE	CUMULATIVE RELEASE RATE (COUNTS/MIN)	SPECIFICATION	CLASS	TEST METHOD
≥ 0.3µm	743*	Less than 2,000	1	IEST-RP-CC003.4
≥ 0.5µm	318*	2,000 - 20,000	1	IEST-RP-CC003.4
≥ 5.0µm	43*	20,000 - 200,000	1	IEST-RP-CC003.4

*Typical results

PERMEATION TEST AGAINST CHEMO DRUGS

CHEMOTHERAPY DRUGS	BREAKTHROUGH TIME	TEST METHOD
Carmustine	30 min	ASTM F739-20
Cisplatin	> 480 min	ASTM F739-20
Cyclophosphamide	> 480 min	ASTM F739-20
Doxorubicin HCl	> 480 min	ASTM F739-20
Etoposide	> 480 min	ASTM F739-20
Fluorouracil	> 480 min	ASTM F739-20
Methotrexate	> 480 min	ASTM F739-20
Paclitaxel	> 480 min	ASTM F739-20
Thiotepa	60 min	ASTM F739-20

*Results achieved under controlled laboratory conditions, by accredited ISO 17025 third party testing laboratory

**Mask not tested

TECHNICAL PROPERTIES

TEST REFERENCE	EXPLANATION	TEST RESULTS	
EN 14325:2004 EN ISO 6530:2005	Repellency to chemicals	10% Sodium hydroxide	Level 3
		30% Sulphuric acid	Level 3
		O-Xylene	Level 2
		Butan-1-ol	Level 2
		70% Isopropyl alcohol	Level 2
		70% Ethanol	Level 2
EN 14325:2004 EN ISO 6530:2005	Resistance to penetration by chemicals	10% Sodium hydroxide	Level 3
		30% Sulphuric acid	Level 3
		O-Xylene	Level 3
		Butan-1-ol	Level 3
		70% Isopropyl alcohol	Level 3
		70% Ethanol	Level 3
EN 14325:2004 EN ISO 9073-4:1997	Trapezoidal tear resistance	Machine direction	Class 2
		Cross direction	Class 2
EN 14325:2004 EN ISO 13934-1:2013	Tensile strength	Machine direction	Class 1
		Cross direction	Class 2
EN 14325:2004 EN ISO 12947-2:2016	Abrasion resistance	Class 2	
EN 14325:2004 EN ISO 7854:1997, Method B	Flex cracking resistance	Class 6	
EN 14325:2004 EN 863:1995	Puncture resistance	Class 1	
EN 14325:2004 [5.5]	Seam strength	Class 2	
EN 13034:2015 + A1:2009 ISO 17491-4:2008 (Type PB6)	Chemical protective coveralls have been tested to the whole suit test and Type PB(6) hoods and sleeves have not been tested to the whole suit test	-	
In-house AQL 1.5	Test plan for major defect	Pass	
EN ISO11137 Part 2:2015	Sterility validation	SAL 10 ⁻⁶	

FACEMASK MATERIALS

Outer layer	Non-woven spunbond polyester
Filtration Layer	Non-woven meltblown polyester
Inner facing layer	Non-woven polypropylene / polyethylene
Tie-tapes	Non-woven polyester

FACEMASK FILTRATION PROPERTIES

Particle Filtration Efficiency (PFE) @ 0.1 Micron	94%
Bacterial Filtration Efficiency (BFE) @ 0.3 Micron	97%
Differential Pressure (ΔP), mm H ₂ O/cm ²	6.8



LOADING

	EURO-PALLET	STANDARD PALLET
Pallet size	W80 L120cm	W100 L120cm
Gross weight	7.29kg	7.29kg
Carton size	W28 L43 H31cm	W28 L43 H31cm
Nett weight	4.82kg	4.82kg
Air freight pallet	Max height: 139cm Layers: 4 Cartons: 24	Max height: 139cm Layers: 4 Cartons: 32
Sea freight pallet	Max height: 170cm Layers: 5 Cartons: 30	Max height: 170cm Layers: 5 Cartons: 40

DOCUMENTATION



CERTIFICATE OF CONFORMANCE (COC)
CERTIFICATE OF ANALYSIS (COA)
CERTIFICATE OF PROCESSING (COP)
Please [email us](#)



FACTORY RELATED CERTIFICATIONS
To request ISO9001 Certificate,
please [email us](#)



Country of origin: **China**
HS Code: 6506109000

This data sheet and any other claims made by or on behalf of Isofield shall not be taken as a warranty of merchantability or as a statement that any Isofield products are suitable for a specific purpose. Isofield shall not be held responsible for the end user's choice of product for a particular application.

EUROPE

ISOFIELD (IRELAND) LTD
70 Northumberland Road, Ballsbridge Dublin 4,
Ireland T +44 (0) 1638 6762 39

ASIA

ISOFIELD SDN BHD
6 Jalan Gudang 16/9, Seksyen 16, 40200, Shah Alam,
Selangor, Malaysia, T +603 5512 1709

CONTACT

www.isofield.com
info@isofield.com